



Eva - Emp 3.0



Easy Slide Out



3 Way Pay

MegaCold L

Description

Here is the new Saeco MegaCold line. This successful line of snack & food machines has a completely new design, with aluminium profiles and modern graphics.

MegaCold L is the new generation of 8-spiral snack & food vending machines with 6 and 7 removable drawers for snacks, cold drinks in cans or bottles and, in the food configuration (3°C), also for sandwiches and fresh products. The widely flexible configurations available create several different combinations offering a wide variety of products. These machines can be successfully paired with the freestanding hot Atlante Evo 500/700 machine.

Accessories

- RS1 programming key
- Eva-Dts kit with infrared connection
- Product compartment reinforcement kit
- Wall mounting brackets kit
- Sandwich compartment kit

Main features

- Energy class A+ machine (EVA - EMP 3.0)
- Programmable temperature (stratified configuration: 6°; 3 food trays: 3°)
- The extraction of the group is very easy and facilitated by sideways (Easy Slide out)
- New silk-printed images for the lower panel
- Multivend up to 3 products with 1 selection
- New electronics
- Possibility to install 3 payment systems at the same time (3 Way Pay)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive payment systems, besides the EVA-DTS system

User interface

- 12-button keypad
- 2-line, 20-character alphanumeric display

Technical data

Structural specifications

Dimensions (w x h x d)	900 x 1830 x 790 mm
Overall size with open door	1660 mm
Weight	260 kg

Electrical specifications

Power supply	230V/50 Hz
Power consumption	450 W
EVA - EMP consumption (idle mode)	228 Wh/h

Other specifications

Number of trays	6 - 7
Bottle tray	48 bottles - h 280 mm
Can tray	48 cans
Snack tray	according to the spiral type
Number of spirals	48 - 56
Available spirals	20 (20 products) to 100 (4 products) pitch
Adjustable temperature	
Stratified configuration snack/can/bottle	6°C - 14°C throughout the cell
Food configuration snack food/Tetra Pak	9°C - 14°C 3-4 upper trays 3°C 3 lower trays

Technical specifications

- Programmable temperature based on product assortment
- The extraction of the group is very easy and facilitated by sideways (Easy Slide Out)
- The slot supports CPU, payment systems, display, keypad and closes the cash box area
- Prepainted galvanized steel-sheet structure
- Photocells
- Height of the cells containing the trays equal to 1250 mm

- Removable plastic trays, which provide a suitable resistance to weight. The tray position can be easily adjusted with 10 mm shifts.
- Self configuration with automatic reset at every machine start
- Programming of sale prices
- LED lighting
- RSI programmable Rielda lock
- Energy class A+ (EVA - EMP 3.0)
- CE approved

CE

